



PENDING CLAIM SET

Applicants note that this listing of claims is provided for the Examiner's convenience and clarification. THIS CLAIM SET IS NOT FOR ENTRY.

1. (Original) A brake system comprising:
 - a normal source of pressurized hydraulic brake fluid;
 - a backup source of pressurized hydraulic brake fluid;
 - a vehicle brake which is operated by application of pressurized hydraulic brake fluid thereto;
 - a valve for selectively preventing the flow of hydraulic brake fluid between the backup source and said vehicle brake; and
 - a fluid separator unit for maintaining the integrity of said backup source of pressurized fluid and preventing intermixing of the hydraulic brake fluid of said normal source and the hydraulic brake fluid of said backup source and having a movable pressure boundary which enables, through movement thereof, said normal source of pressurized hydraulic brake fluid to selectively act upon said vehicle brake via a portion of said backup source when said valve is shut.

2. (Original) The brake system of claim 1, further including a brake system brake demand detection arrangement comprising:

a manually operated master cylinder;

a fluid conduit in fluid communication with said master cylinder;

a pedal simulator in fluid communication with said master cylinder via said fluid conduit, said pedal simulator including a spring and a piston acting to compress said spring under the influence of pressurized hydraulic fluid from said master cylinder exceeding a first pressure;

a pressure transducer generating a signal representative of the pressure of said fluid flowing between said master cylinder and said pedal simulator; and

an expansion volume unit in fluid communication with said master cylinder and said pedal simulator via said fluid conduit, said expansion volume unit permitting fluid to flow from said master cylinder into said expansion volume unit when said fluid exceeds a second pressure less than said first pressure.

3. (Original) The brake system of claim 2 wherein said pedal simulator further includes a housing defining a bore having a first end adapted to be connected in fluid communication with said backup source, said bore further having a second end, said piston being slidably disposed in said bore and having a first face and a second face, said spring engaging said second face of said piston and acting between said piston and a portion of said housing to urge said first face of said piston toward said first end of said bore, and a damping circuit hydraulically interposed between said first end of said bore and said backup source to present a first cross sectional flow area to fluid flowing from said backup source through said damping circuit into said housing, and presenting a second cross sectional flow area to fluid flowing from said housing through said damping circuit, the ratio of said second cross sectional flow area to said first cross sectional flow area being greater than unity.

4. (Original) The brake system of claim 3 wherein said ratio is less than 10:1.

5. (Original) The brake system of claim 4 wherein said ratio is in the range of 2:1 to 4:1.
6. (Original) The brake system of claim 3 further including a relief valve opening above a predetermined pressure to permit fluid flow through said relief valve from said brake system to said housing.
7. (Original) The brake system of claim 6 wherein said predetermined pressure is in the range of about 5 bar to about 30 bar.
8. (Original) The brake system of claim 3 further including a relief valve opening above a predetermined pressure to permit fluid flow through said relief valve from said brake system to said housing.
9. (Original) The brake system of claim 8 wherein said predetermined pressure is in the range of about 5 bar to about 30 bar.
10. (Original) The brake system of claim 2 wherein said fluid separator unit has a housing defining a cylinder bore and a piston slideably disposed therein, said piston having a first working face in fluid communication with said normal source and a second working face in fluid communication with said backup source, said first and second working faces having substantially similar areas.

11. (Original) The brake system of claim 2, further including:
a brake pedal for operating said master cylinder;
a pedal travel sensor for generating a stroke signal representative of the stroke of said brake pedal;
said signal from said pressure transducer being related to the brake application force applied by a driver to said brake pedal;
a control unit responsive to a demand signal for controlling said brake system actuator, said demand signal being generated as a blended function of both said stroke signal and said signal from said pressure transducer wherein, during an initial movement of said brake pedal, said stroke signal is weighted greater than said signal from said pressure transducer, and wherein, during a subsequent movement of said brake pedal, said signal from said pressure transducer is weighted greater than said stroke signal.

12. (Original) The brake system of claim 1 further including a pedal simulator, said pedal simulator comprising:
a housing defining a bore having a first end adapted to be connected in fluid communication with said backup source, said bore further having a second end;
a piston slidably disposed in said bore and having a first face and a second face;
a spring engaging said second face of said piston and acting between said piston and a portion of said housing to urge said first face of said piston toward said first end of said bore; and
a damping circuit hydraulically interposed between said first end of said bore and said backup source to present a first cross sectional flow area to fluid flowing from said backup source through said damping circuit into said housing, and presenting a second cross sectional flow area to fluid flowing from said housing through said damping circuit, the ratio of said second cross sectional flow area to said first cross sectional flow area being greater than unity.

13. (Original) The brake system of claim 12 wherein said ratio is less than 10:1.

14. (Original) The brake system of claim 13 wherein said ratio is in the range of 2:1 to 4:1.

15. (Original) The brake system of claim 12 further including a relief valve opening above a predetermined pressure to permit fluid flow through said relief valve from said brake system to said housing.

16. (Original) The brake system of claim 15 wherein said predetermined pressure is in the range of about 5 bar to about 30 bar.

17. (Original) The brake system of claim 1 wherein said fluid separator unit has a housing defining a cylinder bore and a piston slideably disposed therein, said piston having a first working face in fluid communication with said normal source and a second working face in fluid communication with said backup source, said first and second working faces having substantially similar areas.

18. (Original) A brake system comprising:
a brake pedal for operating a brake system actuator;
a pedal travel sensor for generating a stroke signal representative of the stroke of said brake pedal;
a brake system sensor for generating a force signal representative of the brake application force applied by a driver to said brake pedal;
a control unit responsive to a demand signal for controlling said brake system actuator, said demand signal being generated as a blended function of both said stroke, signal and said force signal wherein, during a first part of the stroke of said brake pedal, said stroke signal is weighted greater than said force signal, and wherein, during a second part of the stroke of said brake pedal, said force signal is weighted greater than said stroke signal.

19. (Original) An electro-hydraulic brake system comprising:

- a reservoir of hydraulic brake fluid;
- a pump having a suction port and a discharge port, said suction port being connected in fluid communication with said reservoir;
- a first fluid conduit being connected in fluid communication with said discharge port of said pump;
- a fluid separator unit having a housing with a bore defined therethrough, said bore having a first end and a second end, said first end of said bore being connected in fluid communication with said discharge port of said pump via said first fluid conduit, said fluid separator unit further including a piston slidingly disposed in said bore and a spring disposed to urge said piston toward said first end of said bore;
- a second fluid conduit connected in fluid communication with said second end of said fluid separator unit;
- a vehicle brake connected in fluid communication with said second end of said fluid separator unit via said second fluid conduit;
- a third fluid conduit connected in fluid communication with said vehicle brake;
- a hydraulic master cylinder connected in fluid communication with said vehicle brake via said third fluid conduit;
- an electrically-operated valve disposed in said third fluid conduit, said valve preventing the flow of hydraulic brake fluid between said master cylinder and said vehicle brake when closed, said valve being open to permit the flow of hydraulic brake fluid between said master cylinder and said vehicle brake when said valve is electrically deenergized;
- a fourth fluid conduit connected in fluid communication with said master cylinder and said third fluid conduit;
- a pedal simulator connected in fluid communication with said master cylinder via said fourth fluid conduit;

an second electrically-operated valve disposed in said fourth fluid conduit, said second valve being closed to prevent the flow of hydraulic brake fluid between said master cylinder and said pedal simulator when said second valve is deenergized, said second valve permitting the flow of hydraulic brake fluid between said master cylinder and said pedal simulator when said second valve is open; and

a damping circuit hydraulically interposed between said master cylinder and said pedal simulator, said damping circuit comprising, in parallel flow paths, an orifice and a check valve such that said damping circuit presents a first cross sectional flow area to fluid flowing from said master cylinder through said damping circuit into said pedal simulator, and presenting a second cross sectional flow area, different from said first cross sectional flow area, to fluid flowing from said pedal simulator to said master cylinder through said damping circuit.

20. (Original) The electro-hydraulic brake system of claim 19 further including a third electrically-operated valve disposed in said first fluid conduit, said third valve preventing fluid communication between said pump and said fluid separator unit when said third valve is closed, said third valve permitting fluid communication between said pump and said fluid separator unit when said third valve is open, the electro-hydraulic brake system further including fifth fluid conduit having a first end connected in fluid communication with said first fluid conduit and said fluid separator unit and having a second connected in fluid communication with said reservoir, the electro-hydraulic brake system further including a fourth electrically-operated valve disposed in said fifth fluid conduit, said fourth valve preventing fluid communication between said fluid separator unit and said reservoir when said fourth valve is closed, said fourth valve permitting fluid communication between said fluid separator unit and said reservoir when said fourth valve is open.

21. (Cancelled).

22. (Amended) A hydraulic brake system for a vehicle comprising:

- wheel brakes for four wheels, in which the wheels are distributed with a first and second wheel brake on a first vehicle axle and a third and a fourth wheel brake on a second vehicle axle;
- a normal hydraulic energy source, having electrically controllable brake valve devices disposed between said energy source and said wheel brakes;
- a brake pedal;
- a sensor generating a first signal indicative of the position of said brake pedal;
- a second sensor generating a second signal indicative of the force exerted by a driver on said brake pedal;
- a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each brake circuit being in fluid communication with at least one of said wheel brakes;
- a respective normally open isolation valve being disposed between said master cylinder and said wheel brakes in each of said two brake circuits, each of said isolation valves being switched into a closed position when said wheel brakes are supplied with fluid from said normal hydraulic energy source;
- a respective fluid separator unit being interposed between each of said first and second wheel brakes of said first vehicle axle and an associated one of the electrically controllable brake valve devices, said fluid separator units having movable components forming a pressure boundary that enables said normal source to selectively act upon said vehicle brake via a portion of said backup source, said first and second wheel brakes being connected to a respective one of said isolation valves associated with said two brake circuits of said master cylinder; and
- a control unit for controlling said normal hydraulic energy source and said isolation valves, said control unit responding as a blended function of both said first signal and said second signal, with the contribution of the second signal relative to the first signal generally varying as a function of the first signal.

23. (Amended) The hydraulic brake system of Claim 18, further comprising:

wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;

a normal source of pressurized hydraulic brake fluid, having electrically controllable brake valve devices disposed between said normal source and said wheel brakes,

a master cylinder comprising at least a portion of said brake system actuator and supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and

a respective normally open isolation valve being disposed between said master cylinder and said respective one of said wheel brakes in each brake circuit, each of said isolation valves being electrically switched into a closed position when said wheel brakes are supplied with fluid from said normal source, and wherein at least the electrically controllable brake valve devices are controlled by said control unit.

24. (Previously Presented) The hydraulic brake system of Claim 23, said normal source including a motor driven pump for pumping hydraulic brake fluid from a reservoir, wherein said electrically controllable brake valve devices are arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

25. (Amended) The hydraulic brake system of Claim 18, further comprising:
wheel brakes for two wheels, in which the wheels are distributed at each end of
a front vehicle axle;

a hydraulic fluid reservoir;

a normal source of pressurized hydraulic brake fluid, having a motor-driven
pump for pumping hydraulic brake fluid from said reservoir;

a master cylinder comprising at least a portion of said brake system actuator
and supplying two brake circuits, said master cylinder being actuated by said brake
pedal and being intended for carrying out a backup brake operation by muscle-
powered energy via said brake pedal, each of said brake circuits being in fluid
communication with a respective one of said wheel brakes; and

a respective electrically controllable brake valve device associated with each of
said wheel brakes, said electrically controllable brake valve devices being arranged to
block a respective flow path from said normal source to said wheel brakes and to open
a respective flow path from said wheel brakes to said reservoir when no braking is
being demanded.

26. (Previously Presented) The brake system of Claim 1, further
comprising:

a second vehicle brake, said vehicle brake and said second vehicle brake being
mounted on an axle of a vehicle, said normal source of pressurized hydraulic brake
fluid adapted to selectively supply hydraulic brake fluid to said vehicle brake and said
second vehicle brake, said backup source of pressurized hydraulic brake fluid
comprising a master cylinder;

a first backup fluid conduit extending between said master cylinder and said
first vehicle brake to selectively provide fluid communication between said backup
source and said first vehicle brake; and

a second backup fluid conduit extending between said master cylinder and said
second vehicle brake to selectively provide fluid communication between said backup
source and said second vehicle brake.

27. (Previously Presented) The brake system of Claim 1, further comprising:

a second vehicle brake, said vehicle brake and said second vehicle brake distributed on a first vehicle axle;

a third and a fourth vehicle brake on a second vehicle axle;

a normal hydraulic energy source, having electrically controllable brake valve devices disposed between said energy source and said vehicle brakes;

a brake pedal;

a first brake system sensor that is actuated by said brake pedal, for carrying out brake operations by operation of the electrically controllable brake valve devices;

a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each brake circuit being in fluid communication with at least one of said vehicle brakes;

a respective normally open isolation valve being disposed between said master cylinder and said vehicle brakes in each of said two brake circuits, each of said isolation valves being switched into a closed position when said vehicle brakes are supplied with fluid from said normal hydraulic energy source, and wherein at least the electrically controllable brake valve devices are controlled by a control unit; and

a respective fluid separator unit being interposed between each of said first and second vehicle brakes of said first vehicle axle and an associated one of the electrically controllable brake valve devices, said first and second vehicle brakes being connected to a respective one of said isolation valves associated with said two brake circuits of said master cylinder.

28. (Previously Presented) The brake system of Claim 1, further comprising:

a second vehicle brake, each of said vehicle brake and said second vehicle brake comprising respective wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;

said normal source of pressurized hydraulic brake fluid having electrically controllable brake valve devices disposed between said normal source and said wheel brakes, said electrically controllable brake valve devices being controlled by a control unit in response to a braking demand signal;

a brake pedal;

said backup source comprising a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and

a respective normally open isolation valve being disposed between said master cylinder and said respective one of said wheel brakes in each brake circuit, each of said isolation valves being electrically switched into a closed position when said wheel brakes are supplied with fluid from said normal source, one of said normally open isolation valves comprising said valve for selectively preventing the flow of hydraulic brake fluid between the backup source and said vehicle brake.

29. (Previously Presented) The brake system of Claim 28, said normal source including a motor driven pump for pumping hydraulic brake fluid from a reservoir, wherein said electrically controllable brake valve devices are arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

30. (Previously Presented) The brake system of Claim 1, further comprising:

a second vehicle brake, each of said vehicle brake and said second vehicle brake comprising respective wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;

a hydraulic fluid reservoir;

said normal source of pressurized hydraulic brake fluid having a motor-driven pump for pumping hydraulic brake fluid from said reservoir;

a brake pedal;

said backup source of pressurized hydraulic fluid comprising a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and

a respective electrically controllable brake valve device associated with each of said wheel brakes, said electrically controllable brake valve devices being arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

31. (Previously Presented) The brake system of Claim 18, further comprising:

an axle of a vehicle;

a first wheel brake mounted on said axle;

a second wheel brake mounted on said axle;

a normal source of pressurized hydraulic brake fluid adapted to selectively supply hydraulic brake fluid to said first wheel brake and said second wheel brake;

a backup source of pressurized hydraulic brake fluid comprising a master cylinder;

a first backup fluid conduit extending between said master cylinder and said first wheel brake to selectively provide fluid communication between said backup source and said first wheel brake; and

a second backup fluid conduit extending between said master cylinder and said second wheel brake to selectively provide fluid communication between said backup source and said second wheel brake.

32. (Previously Presented) The brake system of Claim 18, further comprising:

wheel brakes for four wheels, in which the wheels are distributed with a first and second wheel brake on a first vehicle axle and a third and a fourth wheel brake on a second vehicle axle;

a normal hydraulic energy source, having electrically controllable brake valve devices disposed between said energy source and said wheel brakes;

said brake system sensor actuated by said brake pedal, for carrying out brake operations by operation of the electrically controllable brake valve devices;

a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each brake circuit being in fluid communication with at least one of said wheel brakes;

a respective normally open isolation valve being disposed between said master cylinder and said wheel brakes in each of said two brake circuits, each of said isolation valves being switched into a closed position when said wheel brakes are supplied with fluid from said normal hydraulic energy source, and wherein at least the electrically controllable brake valve devices are controlled by a control unit; and

a respective fluid separator unit being interposed between each of said first and second wheel brakes of said first vehicle axle and an associated one of the electrically controllable brake valve devices, said first and second wheel brakes being connected to a respective one of said isolation valves associated with said two brake circuits of said master cylinder.

33. (Previously Presented) The brake system of Claim 18, further comprising:

wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;

a normal source of pressurized hydraulic brake fluid, having electrically controllable brake valve devices disposed between said normal source and said wheel brakes, said electrically controllable brake valve devices being controlled by a control unit in response to a braking demand signal;

a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and

a respective normally open isolation valve being disposed between said master cylinder and said respective one of said wheel brakes in each brake circuit, each of said isolation valves being electrically switched into a closed position when said wheel brakes are supplied with fluid from said normal source.

34. (Previously Presented) The hydraulic brake system of Claim 33, said normal source including a motor driven pump for pumping hydraulic brake fluid from a reservoir, wherein said electrically controllable brake valve devices are arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

35. (Previously Presented) The brake system of Claim 18, further comprising:

wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;

a hydraulic fluid reservoir;

a normal source of pressurized hydraulic brake fluid, having a motor-driven pump for pumping hydraulic brake fluid from said reservoir;

a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and

a respective electrically controllable brake valve device associated with each of said wheel brakes, said electrically controllable brake valve devices being arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

36. (Amended) A brake system comprising:

- an axle of a vehicle;
- a first wheel brake mounted on said axle;
- a second wheel brake mounted on said axle;
- a normal source of pressurized hydraulic brake fluid adapted to selectively supply hydraulic brake fluid to said first wheel brake and said second wheel brake;
- a backup source of pressurized hydraulic brake fluid comprising a master cylinder;
 - a first backup fluid conduit extending between said master cylinder and said first wheel brake to selectively provide fluid communication between said backup source and said first wheel brake;
 - a second backup fluid conduit extending between said master cylinder and said second wheel brake to selectively provide fluid communication between said backup source and said second wheel brake; and
 - a respective valve arrangement being disposed between said master cylinder and said wheel brakes in each of said first backup fluid conduit and said second backup fluid conduit and having a movable component forming a pressure boundary which enables said normal source of pressurized hydraulic brake fluid to selectively act upon said respective vehicle brakes via a portion of said backup source.

37. (Amended) A hydraulic brake system for a vehicle comprising:

- wheel brakes for four wheels, in which the wheels are distributed with a first and second wheel brake on a first vehicle axle and a third and a fourth wheel brake on a second vehicle axle;
- a normal hydraulic energy source,
- electrically controllable brake valve devices disposed between said energy source and said wheel brakes;
- a brake pedal;
- a first brake system sensor that is actuated by said brake pedal, for carrying out brake operations by operation of the electrically controllable brake valve devices;
- a master cylinder actuated by said brake pedal and intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal,
- two brake circuits supplied by said master cylinder, each brake circuit being in fluid communication with at least one of said wheel brakes;
- a respective normally open isolation valve being disposed between said master cylinder and said wheel brakes in each of said two brake circuits, each of said isolation valves being switched into a closed position when said wheel brakes are supplied with fluid from said normal hydraulic energy source, and wherein at least said isolation valves are controlled by a control unit; and
- a respective fluid separator unit being interposed between each of said first and second wheel brakes of said first vehicle axle and an associated one of the electrically controllable brake valve devices, said first and second wheel brakes being connected to a respective one of said isolation valves associated with said two brake circuits of said master cylinder, said fluid separator units having movable components that cooperate to enable said normal source of pressurized hydraulic brake fluid to selectively act upon said respective vehicle brakes via a portion of said backup source.

38. (Amended) A hydraulic brake system for a vehicle comprising:
wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;
a normal source of pressurized hydraulic brake fluid, having electrically controllable brake valve devices disposed between said normal source and said wheel brakes;
a brake pedal;
a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and
a respective normally open isolation valve being disposed between said master cylinder and said respective one of said wheel brakes in each brake circuit, each of said isolation valves being electrically switched into a closed position when said wheel brakes are supplied with fluid from said normal source, and at least the electrically controllable brake valve devices being controlled by a control unit in response to a braking demand signal, each of said isolation valves having a movable component, said isolation valves cooperating with one another to form a pressure boundary that enables said normal source of pressurized hydraulic brake fluid to selectively act upon said vehicle brake via a portion of said backup source.

39. (Previously Presented) The hydraulic brake system of Claim 23, said normal source including a motor driven pump for pumping hydraulic brake fluid from a reservoir, wherein said electrically controllable brake valve devices are arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded.

40. (Amended) A hydraulic brake system for a vehicle comprising:
wheel brakes for two wheels, in which the wheels are distributed at each end of a front vehicle axle;
a hydraulic fluid reservoir;
a normal source of pressurized hydraulic brake fluid, having a motor-driven pump for pumping hydraulic brake fluid from said reservoir;
a brake pedal;
a master cylinder supplying two brake circuits, said master cylinder being actuated by said brake pedal and being intended for carrying out a backup brake operation by muscle-powered energy via said brake pedal, each of said brake circuits being in fluid communication with a respective one of said wheel brakes; and
a respective electrically controllable brake valve device associated with each of said wheel brakes, said electrically controllable brake valve devices being arranged to block a respective flow path from said normal source to said wheel brakes and to open a respective flow path from said wheel brakes to said reservoir when no braking is being demanded, said respective valve devices cooperating to form a fluid separator having a movable pressure boundary that enables said normal source of pressurized hydraulic brake fluid to selectively act upon said respective vehicle brakes via a portion of said backup source.

41. (Previously Presented) The hydraulic brake system of Claim 31, wherein said normal source is under the control of said control unit.

42. (Previously Presented) A brake system comprising:
a vehicle brake;
a normal fluid source supplying a first fluid;
a backup fluid source supplying a second fluid;
a structure for receiving said first fluid and said second fluid for operation of the vehicle and having a movable pressure boundary for preventing intermixing of said first fluid and said second fluid while said vehicle brake is operating;
a first sensor generating a first output signal;
a second sensor generating a second output signal;
a control unit responsive to a demand signal for controlling the operation of said vehicle brake, said demand signal being generated as a blended function of both said first output signal and said second output signal.

43. (Previously Presented) The brake system of Claim 42, wherein said movable pressure boundary comprises a piston.

44. (Previously Presented) The brake system of Claim 42, further including a brake pedal, and wherein said demand signal is blended as a function of the position of said brake pedal.

45. (Previously Presented) The brake system of Claim 44, wherein said first output signal is representative of the position of said brake pedal, and the relative contributions of the first output signal and the second output signal to the demand signal is blended as a function of the position of said brake pedal.

46. (Previously Presented) The brake system of Claim 42, wherein said first output signal and said second output signal work in accordance with different principles and generate different output signals.

47. (Previously Presented) The brake system of Claim 42, wherein said structure is a fluid separator.

48. (New) A brake system comprising:
a brake pedal for operating a brake system actuator;
a pedal travel sensor for generating a stroke signal representative of the stroke of said brake pedal;
a brake system sensor for generating a second signal representative of a brake system parameter other than the stroke of said brake pedal;
a control unit responsive to a demand signal for controlling said brake system actuator, said demand signal being generated as a blended function of both said stroke signal and said second signal wherein, during a first part of the stroke of said brake pedal, said stroke signal is weighted greater than said second signal, and wherein, during a second part of the stroke of said brake pedal, said second signal is weighted greater than said stroke signal.

49. (New) A hydraulic brake system for a vehicle comprising:
wheel brakes for two wheels, in which the wheels are distributed at each end of
a front vehicle axle;

a normal source of pressurized hydraulic brake fluid, having electrically
controllable brake valve devices disposed between said normal source and said wheel
brakes;

a brake pedal;

a master cylinder supplying two brake circuits, said master cylinder being
actuated by said brake pedal and being intended for carrying out a backup brake
operation by muscle-powered energy via said brake pedal, each of said brake circuits
being in fluid communication with a respective one of said wheel brakes, said master
cylinder being in fluid communication with at least one of said wheel brakes upon at
least one of loss of electrical power at said electrically controllable brake valve
devices and loss of pressure in the normal source; and

a respective normally open isolation valve being disposed between said master
cylinder and said respective one of said wheel brakes in each brake circuit, each of
said isolation valves being electrically switched into a closed position when said wheel
brakes are supplied with fluid from said normal source, and at least the electrically
controllable brake valve devices being controlled by a control unit in response to a
braking demand signal, each of said isolation valves having a movable component,
said isolation valves cooperating with one another to form a pressure boundary that
enables said normal source of pressurized hydraulic brake fluid to selectively act upon
said vehicle brake via a portion of said backup source.